

# Bona AntiSlip

PART OF THE BONA ADDITIVE+ RANGE

## Enhanced Slip Resistance



Bona AntiSlip is designed to boost the slip resistance of your chosen Bona finish, increasing safety in areas with a higher risk of slips and falls caused by spillages, such as commercial premises, kitchens, entrances, and stairways.

Anti-slip properties were previously exclusive to Bona Traffic HD Anti-Slip and Bona Traffic HD Raw. With the introduction of Bona AntiSlip, you can now extend this functionality to a wider range of finishes, for both wood and resilient flooring, offering you greater flexibility.

- Reduces slip risk
- For wood and resilient floors
- Slip resistance according to AS 4586:2013
- Suitable for recoating treatments

# Bona AntiSlip

## PART OF THE BONA ADDITIVE+ RANGE

### Enhanced Slip Resistance

#### TECHNICAL DATA

<b>Mixing ratio:</b>	1 bottle (125 g) to 5 litres finish
<b>Safety:</b>	Unclassified.
<b>Shelf life:</b>	4 years from date of production in unopened original container.
<b>Disposal:</b>	Empty containers should be recycled. Waste must be disposed of at an approved waste disposal facility - do not pour down drains or sewers. Follow all local waste regulations.
<b>Pack size:</b>	125 g bottle
<b>Certificates &amp; standards:</b>	Bona AntiSlip achieves: P3 / P4 / R10 (AS 4586:2013) in combination with selected Bona finishes. See <a href="http://www.bona.com.au">www.bona.com.au</a> for certificates and the slip resistance ratings available.

*Additional detailed information is noted in the appropriate Safety Data Sheet.*

#### PREPARATION

Bona AntiSlip should be added to the final coat of finish. Follow the normal preparation, treatment schedule and application instructions for the chosen finish up until the final coat.

**Note:** Bona AntiSlip affects the gloss level, resulting in a more matt appearance. If uncertain, carry out a test before full application.

#### COMPATIBLE WITH:

If certified slip resistance is required, please consult the Bona AntiSlip product page at [bona.com.au](http://bona.com.au) for the current list of certificates.

Product	P Rating	R-Rating	Sheen (%)
Bona Traffic HD Silk Matt	P4	R9	17
Bona Traffic HD Matt	P4	R9	14
Bona Traffic HD Extra Matt	P4	R10	7
Bona Traffic GO Silk Matt	P3	R9	17
Bona Traffic GO Matt	P3	R9	12
Bona Wave Matt	P3	R10	14

# Bona AntiSlip

## PART OF THE BONA ADDITIVE+ RANGE

### Enhanced Slip Resistance

## APPLICATION

1) Add the entire contents of one bottle of Bona AntiSlip Additive (125 g) to one 5 L can of Bona finish. Shake vigorously for at least 60 seconds, turning the can upside down several times to ensure even distribution.

Do not attempt to portion the additive. Only mix full bottles with full cans. If the mixture is stored for later use, clearly mark the can and shake thoroughly as described above before further use.

2) For Bona Traffic GO (a finish without a separate Hardener), proceed directly to step 4.

3) Add the Hardener and shake the can vigorously for a further 60 seconds, again turning the can upside down during shaking to ensure the Hardener is fully mixed with the finish. Allow the mixture to stand for 5 minutes.

N.B. Smaller quantities may be prepared in a Bona Mixing Bottle using the appropriate amount of Hardener.

4) Fit the supplied plastic cone and fine filter before application. This helps prevent any small clumps of additive from being deposited on the floor surface.

5) Apply the finish in accordance with the normal application guidelines and coverage rates stated in the relevant Bona Technical Data Sheet.

Follow the standard guidelines in the relevant Technical Data Sheet regarding drying time, resumption of foot traffic, replacement of furniture, and covering with mats.

## MAINTENANCE

Cleaning with the correct products is easy. When you choose Bona cleaning and maintenance products, you can relax knowing that you have chosen the best possible product to help you care for your floor.

End-user maintenance instructions are available at [www.bona.com.au](http://www.bona.com.au) Please give the end user a digital or print copy.

Note: Bona Polish or Bona Refresher should never be used on an AntiSlip surface, as such products may negatively affect the slip resistance of the floor surface.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and extensive testing but makes no claim to be complete. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice from Bona before use. Bona can only guarantee its products and not the construction as a whole. Observe recommendations from flooring manufacturer and the provisions of relevant standards.