



Bona White

WATERBORNE PRIMER

A Scandinavian, whitewashed look without adding stain or caustic bleach.



Bona White is a pigmented waterborne primer for untreated wood floors designed to give a whitewashed appearance on light to medium coloured wood species. The intensity and depth of colour can be controlled by applying it in one, two or more layers. Excellent levelling properties paired with a good open time promote an even distribution of pigmentation creating wood floors with a beautiful and genuine whitewashed look. For an optimal appearance, pair with Extra Matt Bona Traffic HD (incl. Raw), Bona Traffic GO or Bona Mega EVO.

Bona White dries to a clear film with good resistance to tannins found in wood. Please note though, the product cannot prevent the wood itself from changing colour over time due to the effects of UV light or the migration/movement of natural oils, tannins and other substances present in wood.

With VOC levels below 3% and EC1^{PLUS} certification for very low emissions, the lacquer contributes to good working conditions with a low impact on the indoor air quality.

- Whitewashed look
- Easy roller application
- EC1^{PLUS} certified for very low indoor air emissions

2025-03-25

This data sheet replaces all previous versions, please check bona.com.au to ensure you have the latest version.



Bona White

WATERBORNE PRIMER

A Scandinavian, whitewashed look without adding stain or caustic bleach.

TECHNICAL DATA

Type of lacquer:	Tinted 1-component waterborne acrylate / polyurethane primer
Solids content:	30%
Dilution:	Do not dilute. For improved long-term colour stability, Bona Blocker can be added (See separate datasheet).
Drying time:	1 - 2 hours (20° C / 60% R.H)
Application tools:	Bona Roller (microfiber / fleece) or Bona Swivel Head Bar Applicator
Application rate:	10 - 12 m ² / L per coat
Safety:	Unclassified
Cleaning:	Wipe tools free from residual material. Clean with a minimum of water. Remove dried material with acetone.
Shelf life:	1 year from date of production in unopened original container
Storage/transport:	The temperature must not fall below +5° C or exceed +30° C during storage or transport
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Pack size:	5 litres
Certifications:	EMICODE: EC1 ^{PLUS} (very low emissions)

Additional detailed information is noted in the appropriate Safety Data Sheet.

PREPARATION

Ensure the floor is acclimatised to its end-use environment. The surface must be sanded back to bare wood, dry and free from sanding dust, oil, wax and other contamination. Sanding with a 120 grit abrasive using a Bona Quattro Disc, or similar equipment is recommended for the final sanding of the wood.

Allow the product to reach room temperature. Optimal application conditions are between 18 - 25° C and 30 - 60% relative air humidity. High temperatures and low humidity shorten drying times whereas low temperatures and high humidity lengthen drying time. **Minimum temperature for use is 13° C.**

It is strongly recommended that a sample of the intended specification is prepared to assess the colour and general appearance of the system prior to use.

TREATMENT SCHEDULE

Bona White is most suited for use on lighter "blonde" wood floors to further enhance and emphasise the natural light colour of the species. To improve the long-term colour stability Bona Blocker can be added to Bona White. Bona White is not recommended for use on darker or "red" timbers as satisfactory "coverage" of the original colour will not be achieved, even by multiple applications.



Bona White

WATERBORNE PRIMER

A Scandinavian, whitewashed look without adding stain or caustic bleach.

Typical treatment schedule:

Option 1: 2 x Bona White + 1 x Bona Lacquer

Option 2: 1 x Bona White + 2 x Bona Lacquer

Additional applications of Bona White may be made to increase the depth and brightness of the colour achieved.

For the best appearance, use Bona White with Extra Matt versions of Bona Traffic HD (incl. Raw), Bona Traffic GO or Bona Mega EVO. Do not use Bona Mega with Bona White if you are looking to achieve a true, white look.

Note:

- Bona White is primarily intended for strip and plank floors. It is recommended that application is made “with” the boards/grain wherever possible. The risk of visible application marks increases if Bona White is used on parquetry or other “patterned” floors which require product to be applied across the grain of the wood or laying pattern. Success is possible on such floors, but additional care is needed to ensure an even application of the product without application marks.
- It is not recommended to apply more than two full coats of primer and/or lacquer per day due to risk of excessive wood swelling.
- Bona White must only be used directly onto raw wood. It must not be used in conjunction with stains, oil systems or to overcoat other finishes.

APPLICATION

1. Shake the container well before use and insert the supplied filter. Before using, filter Bona White through a fine external strainer, such as Bona Filter bags - AT31465120, to minimise the potential for undispersed pigment / particles being applied to the floor. Pour the finish into a clean, dry container.
2. Apply Bona White evenly, finishing with the grain, using a Bona Roller (microfiber/fleece) or Bona Swivel Head Bar Applicator at approx. 10 - 12 m² / L, avoiding accumulations of product.
3. When dry (approx. 1 - 2 hours), abrade gently using the Bona Scrad System and Wing 150 grit or finer. Bona Diamond Abrasives 120 grit are also suitable. This must be done after each application of Bona White to reduce grain raising and to even out minor colour variations.
4. Remove all sanding dust before continuing coating
5. If a more intense white look is desired multiple layers of Bona White can be applied. Note: using multiple applications may ‘hide’ the grain pattern of the wood.

2025-03-25

This data sheet replaces all previous versions, please check bona.com.au to ensure you have the latest version.



Bona White

WATERBORNE PRIMER

A Scandinavian, whitewashed look without adding stain or caustic bleach.

6. Finish the treatment with a minimum of one layer of the recommended lacquers. All floors in commercial locations must receive 2 applications of the finishing product, irrespective of the number of applications of Bona White.

IMPORTANT!

- Do not use Bona White as the final treatment for wood floors. Always finish with a topcoat application.
- Plasticisers found in materials such as carpet underlays, furniture legs, castors and adhesives used for fixing can lead to softening and discolouration. Exposure to hair dyes or rubber tyres on cycles, baby strollers, etc can lead to permanent, irreversible discolouration of the surface. Use protection or avoid contact completely.
- Spills should be removed promptly. Unattended spills may cause cosmetic stains or damage the surface.
- Please note that whilst Bona lacquers are designed to provide a sealed surface that is resistant to wear, scuffing and spillage, etc. no surface applied finish system can prevent physical damage to the timber or “harden” the floor. Indentations in the wood and scratches may be caused by furniture, dropped items, dog claws, etc. and steps should be taken to reduce the possibility of this occurring.
- Bona lacquers are non-yellowing and do not change colour due to the effects of UV light. However, Bona lacquers cannot prevent the wood itself changing colour due to tannin bleed, the movement of natural oils or the effects of UV light.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and extensive testing but makes no claim to be complete. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice from Bona before use. Bona can only guarantee its products and not the construction as a whole. Observe recommendations from flooring manufacturer and the provisions of relevant standards.

2025-03-25

This data sheet replaces all previous versions, please check bona.com.au to ensure you have the latest version.