Bona Wood Floor Deep Cleaner

Bona Wood Floor Deep Cleaner is Bona's most powerful cleaner yet. Its oxygenated formula loosens and removes heavy build-up, providing a deep clean without extra effort. For the best result, use Wood Floor Deep Cleaner with the Bona Deep Clean Pad with PowerLoop® technology.

Supplied ready to use, Bona Wood Floor Deep Cleaner is designed for timber floors finished with a polyurethane or hard-wax oil coating system.

- Oxygenated formula removes heavy dirt build-up
- Use with Bona Deep Clean pad with PowerLoop technology
- Safe for wood floors with a polyurethane or hard-wax oil coating system
- Quick & easy cleaning

Technical data

pH-value:	Approx. 4.5 - 5.5
Shelf life:	3 years from date of production in unopened original container
Storage / transport:	The temperature must not fall below +5° C or exceed +25° C during storage and transport.
Disposal:	Empty containers are recyclable as hard plastic.
Content:	<5% nonionic surfactants, oxygen-based bleaching agents
Sizes:	1 litre spray bottle / 2.5 Lt refill / 850 ml refill cartridge for Bona Spray Mop
Certification	Greenguard GOLD

Preparation

Remove loose dust / grit etc. using a vacuum cleaner, Bona Dusting pad or another dry cleaning method. It is important that the floor is cleaned before wet cleaning is carried out.

Application

1. Spray a few square metres of the floor with Wood Floor Deep Cleaner. Let the cleaner work for a minute or so on the surface.

2. Wipe / rub the surface using a Bona Deep Clean Pad. It is very important to rinse the Deep Clean pad well or replace it when it becomes dirty; cleaning pads cannot not remove further dirt / material when already full.

To remove stubborn spots, rubber heel marks, sticky spills, etc. spray Wood Floor Deep Cleaner directly onto the affected area. Allow it to work for a few minutes and then scrub the spot clean with a Bona Deep Clean Pad.

Bona Wood Floor Deep Cleaner is safe for use on oiled floors. However, any cleaning with a detergent system will gradually reduce the protection of a penetrating oil finish system. It is recommended that oiled floors are treated with a maintenance application once the surface starts to look dull or worn.

Important notes

The information provided is prepared to the best of our current knowledge and makes no claim to be complete. The User is responsible for establishing that the product and recommendations herein are fit for the designated purpose, wood type and present situation before use. Bona can only guarantee the delivered product. A professional and thereby successful application of the product is beyond our control. If in doubt make a preliminary test. The User is required to read and understand all information contained on package labels and safety data sheets before using this product.

Bona®

Phone 1300 882 806