# A Traffic for every use

Five different Traffic coatings to suit every application











Bona'





## The solution for high traffic areas

The Bona Traffic range is amongst the world's toughest and fastest drying finishes. The Traffic range provides an unrivalled level of protection, performance and durability for timber flooring environments which are exposed to extreme wear.

All Bona Traffic finishes are non-toxic water-based 100% polyurethane with low VOC solvent content. The Traffic Range consists of five different coatings, each tailored to a specific heavy duty usage.

- ✓ Water-based
- ✓ 100% polyurethane
- ✓ Extreme wear resistance
- ✓ Non-Toxic
- ✓ Low-odour, non-yellowing
- ✓ Fast drying

# Bona Traffic finishes are the market leader

Bona Traffic finishes are designed to last many years in high traffic commercial environments such as restaurants, museums, art galleries and retail outlets where durability is essential. In Australia Bona Traffic finishes have been used to protect some of our most prestigious floors.

### State Library Victoria, VIC



Bona Traffic was used to protect 8,800m<sup>2</sup> of flooring at the State Library of Victoria over a five year redevelopment project.

#### National Gallery of Australia, ACT



Bona Traffic HD satin was used on over 2,000m<sup>2</sup> of floor space at the National Gallery, Australia's premier gallery in our national capital.

### Parliament House, ACT



The heritage floors of Old Parliament House were refinished with Bona Traffic HD to protect against the more than 350,000 visitors each year.

Bona's low VOC's means there is no need to vacate premises during application due to solvent fumes and no concern about the health effects of toxic chemicals.

### Who is Bona?

using this product.





# The Non-toxic, Sustainable Choice



All Bona floor finishes are non-toxic water-based coatings. The main difference between toxic solvent based coatings and non-toxic water-based coatings is the amount of Volatile Organic Compounds (VOC's) that evaporate as the finish dries.

• The market leader in non-toxic timber floor finishes globally • Bona products are available in over 90 countries • The No1 choice for professional contractors • Experts in floor coatings & cleaning products since 1919

Please read the additional information regarding Bona finishes, including technical datasheets, safety information and slip resistance certificates at bona.com.au before

> Bona's floor finishes are GREENGUARD indoor air quality certified, which means they are safe for use around your home, your family and your pets.



Bona **Traffic Range** 



### **Extreme Wear Resistance** for High Traffic Floors



erp Distributed in Australia by EFP Ph: 1300 882 806

### Bona Traffic

#### All Round Coating for High Traffic Areas

Bona Traffic is the ideal all round solution. Perfect for use in heavy traffic residential applications as well as commercial use. Bona Traffic is a commercial grade wear resistant finish with proven performance on more than 350 million m<sup>2</sup> of flooring. In standard tests, Traffic has been shown to have about twice the wear resistance of ordinary water-based products - hence the name.

Traffic is the right choice for busy homes as well as commercial situations such as offices, studios, galleries, public buildings and shops.

- Two-component water-based top coat
- 100% polyurethane
- Excellent wear resistance
- Non-toxic, low odour
- Non-yellowing and unaffected by UV light
- For use with Bona primers
- TVOC 88 g/Lt (av all sheens)
- 8-10 m<sup>2</sup>/Lt coverage
- Drying time 3-4 hours between coats
- 2 sheen levels: Satin and Matt
- Gloss Level (60°):
- Satin 45%
- 15% Matt





# Bona Traffic GO

### Next Generation Heavy Wear Coating

Bona Traffic GO combines the simplicity of a one-component finish with the durability and superior performance of a twocomponent product. Traffic GO is designed for high traffic floors in both residential and commercial situations.

With Traffic GO there is no need to calculate and mix an external hardener with the finish. So there is zero wastage and no worrying about pot life. You now have a simpler, safer way to achieve high traffic commercial durability.

With rapid cure technology Traffic GO reaches maximum hardness in as little as 3 days. In normal circumstances floors can be put back into full use just 24 hours after being completed.

- One-component water-based top coat with two-component performance
- 100% polyurethane
- Ready to apply no mixing required •
- Built-in hardener activates when applied .
- Excellent wear resistance
- Non-toxic, low odour
- Non-yellowing and unaffected by UV light
- Isocyanate & PFAS free
- No waste pot life not applicable
- For use with Bona primers
- Max 3% VOC
- Drying time 2-3 hours between coats
- 3 sheen levels: Satin, Matt and Extra Matt
- Gloss Level (60°): Satin 45% 20% Matt Extra Matt 10%





# Bona Traffic HD

### Extreme Wear Resistance & Minimal Downtime

Bona Traffic HD is designed to be used in commercial situations where the level of traffic and the use of the floor is at its most extreme.

Bona Traffic HD has all of the features and benefits of Bona Traffic, but has been specially formulated for added durability and wear resistance together with a much guicker curing time. Under reasonable conditions, commercial floors can be put back into full use 24 hours after being completed.

Bona Traffic HD is the perfect choice for floors where extreme levels of traffic are expected such as shops, halls, museums, galleries and other public places.

- Two-component water-based top coat
- 100% polyurethane
- Extreme wear resistance
- Non-toxic, low odour
- Non-yellowing and unaffected by UV light
- Suitable for over-coating pre-finished floors
- For use with Bona primers
- TVOC 50 g/Lt (all sheens)
- 8-10 m<sup>2</sup>/Lt coverage
- Drying time 2-3 hours between coats
- 2 sheen levels: Satin and Extra Matt
- Gloss Level (60°): Satin 45%
- Extra Matt 10%







# Bona Traffic HD Raw

Bona Traffic HD Raw brings a uniquely true wood experience into the world of finished floors, offering an ultra matt floor surface with a high level of protection.

Bona Traffic HD Raw creates a soft haptic feeling of untreated wood, delivering an astonishing tactile sensation that looks and feels like raw, natural timber - but with the protection of a finish. A pleasure to walk on with excellent slip safety, Bona Traffic HD Raw is great for homes with children and pets as well as commercial floor surfaces.

Bona Traffic HD Raw creates ultra matt floors with great durability - the raw experience of wood, protected.

- Non-yellowing and unaffected by UV light

- TVOC 52 g/Lt

- Gloss Level (60°):











#### Ultra Matt Floors with Haptic Feel & Great Durability

- Two-component water-based top coat
- 100% polyurethane
- Ultra matt haptic feel
- Non-toxic, low odour
- Extreme wear resistance
- Suitable for over-coating pre-finished floors
- P3 Slip-resistance AS 4586:2013
- 8-10 m<sup>2</sup>/Lt coverage
- Drying time 2-4 hours between coats
- Available only in Ultra Matt
  - Ultra Matt 4%



### Bona Traffic HD Anti-slip

#### Walk Safe with Traffic HD Anti-slip

Bona Traffic HD (Heavy Duty) Anti-slip brings the benefits of Bona Traffic HD together with excellent wear, scuff and scratch resistance and a smooth-to-touch surface.

Traffic HD Anti-slip surpasses the P3 rating required for floors and staircases in commercial and domestic buildings and is uniquely formulated with inert non-reactive slip-resistance particles, removing the need to add powder additives on site to achieve slip-resistance.

It is ideal for applications where safety and anti-slip qualities are paramount such as staircases, aged care, entry foyers and reception areas, food courts, cafés and restaurants, public halls, hospitals, medical centres and other public places.

- Two-component water-based top coat •
- 100% polyurethane
- P4 Slip-resistance AS 4586:2013 •
- Non-toxic, low odour
- Non-yellowing and unaffected by UV light •
- Pre-mixed no need for the on-site addition • of slip-resistance additives
- High durability and extreme scratch resistance
- Extremely quick hardness development (possible to use floor in full use following day)
- For use with Bona primers •
- TVOC 50 g/Lt •
- 8-10 m<sup>2</sup>/Lt coverage
- Drying time 2-3 hours between coats •
- Available only in Matt .
- Gloss Level (60°): Matt 15%



